



LABEL DISPENSERS

Designed to accommodate the demands of high volume, high quality production lines, the Advanced Dynamics Junior range of label dispensers are constructed to the highest standards and will provide reliable, accurate label placement on a wide range of products.

The dispensers will apply labels in any orientation and onto any pack position. They can be supplied as part of an Advanced Dynamics bespoke product handling and labelling system, or for integration into proprietary packaging equipment.

Features

- Simple and efficient operation
- Rugged construction
- Accuracy to + or - 0.5mm
- A.C. drives throughout
- Heavy duty label drive
- Variable speed control
- Throughput to 250 labels/min
- 300mm label-roll capacity
- Very low maintenance

Options

- Label width to 245mm
- Thermal transfer coding
- Hot foil coding
- Adjustment setting counters
- Powered adjustment
- Low reel/label out alarm
- Visual/audible system alarms
- Additional product handling
- Speed-linking

TAILOR MADE EQUIPMENT TO SUIT CUSTOMERS' REQUIREMENTS



TECHNICAL DATA

Dispenser Details	Junior 115	Junior 165	Junior 250
Max. label web-width	110mm	160mm	245mm
Min. label web-width	10mm		
Max. label roll diameter	310mm		
Core size	38mm - 75mm		
Web speed	8 - 30 metres/min		
Accuracy	+/- 0.5mm		
Drive system	AC-motor, peak powered clutch/brake		
Power requirements	240v 1ph 50hz 4amp		
Applicator weight	20kg	21kg	22kg
Control box weight	9.5kg		

Dimensions			
Dispenser height	440mm		
Dispenser length	635mm		
Dispenser width	425mm	457mm	560mm
Control box height	240mm		
Control box length	330mm		
Control box depth	250mm		

LABELLING SYSTEMS

PRINT & APPLY

CHECKWEIGHING

PRODUCT HANDLING SYSTEMS

COLLATION & PACKING SYSTEMS

FLAT PRODUCT WRAPPING

STATIC CONTROL

CONVEYING EQUIPMENT

TURNKEY SOLUTIONS

BARCODE SCANNING/ VERIFICATION

CONTRACT SERVICE

CONSUMABLES AND SPARES

FEEDING SYSTEMS

WEB CLEANING SYSTEMS