



SL-77

STAND ALONE SLEEVE APPLICATOR



SPECIFICATIONS

Model	SL-77
Electrical Supply	110/ 220VAC 50/ 60Hz Single Phase
Power Consumption	1KW
Dispense Driver	Stepper Motor
Film Length Range	22mm ~ 150mm
Bottle Diameter	Dia. 30mm ~ Dia.80mm
Bottle Height	35 ~ 350mm
Film Material	PVC, PET, OPS
Film Thickness	0.035mm ~ 0.08mm
Film Roll Inner Core	Dia. 127 ~ 250mm
Film Roll Outer Core	Dia. 400mm
Dimensions	700 mm(W) x 1000 mm(D) x 2000 mm(H)
Net Weight	Approx. 150 Kgs

Film Brush
Down Device



FEATURE

- Stepping motor system for film driver
- Adjustable main structure lifting & diving
- Simple mandrel positioning when changeover
- Delta colored HMI is more convenient for operation and monitoring.
- Every sleeve labeling process is under the Panasonic PLC monitoring control.
- 30 memory slots reduce the changeover times.



OPTIONAL

- CE Specification Set, included Safety Module
- Mark Sensor for print registration
- Integrated Conveyor
- Bottle Screw Feeder System
- Cap Shrink Tunnel
- Triangular Mandrel for different film size
- Vertical Perforation
- Brusher flapper to tamp film down



Advanced Dynamics
Unit 3,
606 Industrial Park,
Staithgate Lane,
Bradford, BD6 1YA



Advanceddynamics.co.uk



@AdvancedDynamics



@ADPackaging



Advanced-dynamics-ltd